

FLOOR LEVELLERS

Levelflex

Flexible, Fibre Reinforced Self Levelling Floor Compound

- Fibre Reinforced and Flexible
- Apply from 2 – 50mm in one application
- Fast Setting, apply ceramic tiles after 3 hours
- Ideal for Plywood & Chipboard overlay
- Apply directly to T & G Floorboards
- Ideal for use over Underfloor Heating
- Apply Decorative vinyls after 24 hours
- Simply mix with water



Levelflex is a flexible, fibre reinforced, protein free cement based formulation designed for smoothing and levelling sub-floors in preparation to applying a floor finish. Levelflex has been developed for levelling surfaces subject to limited movement and/or vibration such as; plywood overlay, T & G floorboards and underfloor heating as well as more common surfaces like sand/cement screed and concrete. Levelflex can be applied to a depth of 50mm in one application. Fast setting, ceramic tiles can be applied after 3 hours, decorative vinyls after 24 hours.

Suitable for application to:

- Sand/cement screed
- Plywood
- Concrete
- Chipboard
- Flooring grade Asphalt & Bitumen
- T & G Floorboards
- Electric Underfloor Heating
- Underfloor Heated screeds
- Anhydrite Screeds
- Existing tiles
- Cement/Sand render
- Vinyl Tiles/Sheets
- Tilebacker Boards

Specification Category:	CT-C35-F7 to BS EN 1381 3:2002
Water Addition:	4.5 – 5 litres of water to 20kg Levelflex
Coverage:	Mixed with 5 litres of water, 20kg will cover 4.2m ² at a depth 3mm
Application Time:	Once mixed, use within 25 – 30 minutes
Working Time:	Once poured, Levelflex remains workable for approx. 20 mins.
Drying Time:	Light foot traffic after 2 - 3 hours.
Application Temperature:	+5°C to +30°C
Pack Sizes:	20kg
Colour:	Grey