# **Wall Grout**

## Water Resistant Wall Tile Grout

- · Fine textured, smooth wall grout
- 1mm 4mm joint widths
- Mould Resistant
- Water Resistant
- Suitable for all types of tiles
- Simply mix with water
- Very easy to apply and clean off



Wall Grout is a fine powder grout specially formulated using carefully selected cements and additives to give a smooth, creamy, controlled workability for grouting wall tiles. Wall Grout is suitable for grouting joint widths up to 4mm wide. When set it is resistant to water and mould growth. Wall Grout is ideal for use in areas subject to prolonged wet conditions such as domestic & commercial showers, bathrooms and kitchens. Wall Grout is suitable for use internally and externally and is unaffected by frost after setting.

\* When mixed with Flexmaster additive, the properties of Wall Grout are enhanced making it suitable for a wider range of application areas and substrates.

#### **Application Areas**

- Domestic & Commercial Showers
- Bathrooms
- Wet Rooms
- Domestic & Commercial Kitchens
- Areas subject to prolonged wet conditions

### **Application Substrates**

- Gypsum Plaster
- Plasterboard
- Existing Tiles
- Concrete Brick/Block
- Tilebacker Boards

#### **Suitable for Grouting:**

- Porcelain
- Ceramics
- Natural Stones
- ivaturai otorio
- Mosaics
- Terracotta
- Quarry

Coverage chart per 5kg unit Wall		kg unit Wall Grout
	Tile Size	3mm Joint Width
	Mosaic: 24 x 24 x 10	1.2m²
l	150 x 150 x 8	10m²
l	300 x 300 x 10	17m²
l	600 x 600 x 10	30m²

Water Addition: 1.8 litres of water to 5kg Wall Grout

Pot Life at 20°C: 45 – 60 minutes

**Curing Time:** - Wall Grout will start to harden after 3 – 4 hours

- Wall Grout will reach final set after 24 hours

- Allow 3 days before contact with water

Colours: Brilliant White & Ivory

Pack Sizes: 1.5kg, 3kg, 3.5kg, 5kg, 10kg and 20kg packs

Specification Category: Conforms to BS EN 13888 Class CG1