

PREPARATION

ta Tanking System

Waterproofing Kit for areas exposed to wet/damp conditions

- Protects water sensitive substrates from exposure to water
- Stabilises water sensitive substrates prior to applying tiles
- Ready to use, easy to apply
- Apply to a large variety of substrates
- Ideal for wet rooms
- Interior use only



Ta Tanking System is an advanced sealing system designed to give a waterproof coating for protection of water sensitive backgrounds such as plaster and plasterboard. Tanking System prepares the substrate in preparation for applying a large variety of tiles. The system produces a barrier to moisture, flexible enough to accommodate light movement and/or vibration which may be expected under normal conditions of use. Tanking System is ideal for areas exposed to wet, damp conditions such as wet rooms, showers and bathrooms.

Tanking System is not suitable for areas subject to permanent water immersion such as swimming pools. Tanking System cannot be used externally.

Application Areas	Application Substrates	In Preparation for:
<ul style="list-style-type: none">• Domestic & Commercial Showers• Bathrooms• Wet Rooms• Areas subject to prolonged wet conditions• Laundry/Utility rooms	<ul style="list-style-type: none">• Sand/Cement Screed & Render• Concrete• Gypsum Plaster• Plasterboard• Plywood• Fibre cement sheets• Concrete Brick/Block	<ul style="list-style-type: none">• Porcelain• Ceramics• Terracotta• Quarry• Natural Stones• Mosaics• Composite• Quartz

Contents:	1 pack contains: 5kg Tanking Slurry, 1ltr Primeplus, 10 metres of reinforcing tape, latex gloves and instructions.
Coverage:	6.2m ²
Drying Time:	Allow 24 hours before tiling
Colour:	Blue