

Standard Set

Standard Setting Wall & Floor Tile Adhesive

- Ideal for when longer working times are required
- Excellent workability and non slip properties
- 3mm – 12mm bed depth
- Ideal in areas subject to prolonged wet conditions
- Simply mix with water
- Interior and Exterior use



Standard Set is a cement based wall and floor tile adhesive formulated to give an extended open time for when longer working times are required. Standard Set has been developed for fixing a variety of tiles to solid substrates such as plastered walls, brick/block and sand/cement screed. Standard Set is suitable for use in areas subject to prolonged wet conditions such as domestic and commercial showers and wet rooms. Standard Set is suitable for use internally and externally and is unaffected by frost after setting.

* *When mixed with Flexmaster additive, Standard Set is suitable for fixing a wider range of tiles to a wider variety of substrates.*

Suitable for application to:	Suitable for fixing:
<ul style="list-style-type: none"> • Sand/Cement Screed • Concrete • Tilebacker Boards • Gypsum Plaster • Concrete Brick/Block 	<ul style="list-style-type: none"> • Ceramics • Terracotta • Quarry

Water Addition:	Approximately 5 litres of water to 20kg Standard Set
Coverage:	20kg will cover 5 – 6m ² at 3mm thin bed application
Pot Life at 20°C:	3 – 4 hours
Grout After:	24 - 48 hours
Colours:	Grey & White
Pack Sizes:	5kg, 10kg and 20kg packs
Specification Category:	Conforms to BS EN 12004 Class C1TE