

GROUTS



Grout 3000

Highly Versatile, Flexible
Wall & Floor Grout



- 2mm – 15mm Joint Widths
- Flexible
- Contains >20% recycled material
- Very easy to apply and clean off
- Simply mix with water, no additives required
- Ideal for wet areas
- Matching silicone sealants

Grout 3000 is a highly versatile wall and floor grout specially formulated using carefully selected cements and additives to give a smooth, creamy, controlled workability. Grout 3000 is flexible and is suitable for use on surfaces subject to limited movement and/or vibration such as plywood overlay, plasterboard and underfloor heating. Grout 3000 is suitable for grouting joints in wall and floor tiles between 2mm – 15mm wide. Grout 3000 has very low permeability making it ideal for areas subject to prolonged or permanent water immersion such as wet rooms and swimming pools. Grout 3000 is suitable for use internally and externally and is unaffected by frost after setting.

* When mixed with Flexmaster additive, the flexible properties of Grout 3000 are enhanced making it suitable for a wider range of substrates e.g. Floorboards.

Application Areas	Application Substrates	Suitable for Grouting:
<ul style="list-style-type: none"> • Domestic & Commercial Showers • Bathrooms • Wet Rooms • Swimming Pools • Domestic & Commercial Kitchens • Areas subject to prolonged wet conditions • Heavy traffic areas such as: <ul style="list-style-type: none"> - Retail/Shopping Outlets - Car Showrooms - Restaurants 	<ul style="list-style-type: none"> • Sand/Cement Screed & Render • Concrete • Gypsum Plaster • Plasterboard • Underfloor Heating • Plywood • Existing Tiles • Concrete Brick/Block • Tilebacker Boards • Anhydrite Screeds • Flooring grade Asphalt & Bitumen 	<ul style="list-style-type: none"> • Porcelain • Ceramics • Terracotta • Quarry • Natural Stones • Mosaics • Composite • Quartz

Coverage chart per 5kg unit Grout 3000

Tile Size	3mm Joint Width	6mm Joint Width	12mm Joint Width
Mosaic: 24 x 24 x 10	1.2m ²	0.6m ²	0.3m ²
150 x 150 x 8	10m ²	5m ²	2.5m ²
300 x 300 x 10	17m ²	9m ²	4.5m ²
600 x 600 x 10	30m ²	15m ²	7.5m ²

Water Addition:

1kg Grout 3000 requires 350ml of water

Pot Life at 20°C:

Approximately 30 - 45 minutes

Curing Time:

- Light Foot traffic after 3 hours
- Grout 3000 will reach final set after 24 hours
- Allow 3 days before contact with water

Colours:

See page 43

Pack Sizes:

5kg packs

Specification Category:

Conforms to BS EN 13888 Class CG2