

Flexigrout

Flexible, Fast Setting Wide Joint Floor & Wall Grout

- 3mm – 15mm Joint Widths
- Flexible
- For use over Plywood overlay and Underfloor Heating
- Fast Setting
- High Durability
- Interior and Exterior use
- Simply mix with water, no additives required



Flexigrout is a flexible, fast setting wide joint floor and wall grout developed for grouting joints in tiles between 3mm – 15mm wide. Flexigrout is ideal for grouting areas subject to limited movement and/or vibration such as plywood overlay and underfloor heating. Flexigrout is suitable for grouting a large variety of tiles. Polymer has been added to the formulation to increase flexibility, adhesion and water resistance. Flexigrout has a coarse texture resulting in a traditional looking finish. Flexigrout is suitable for use internally and externally and is unaffected by frost after setting.

* When mixed with Flexmaster additive, the properties of Flexigrout are enhanced making it suitable for a wider range substrates e.g. Floorboards and areas subject to prolong wet conditions.

Application Areas	Application Substrates	Suitable for Grouting:
<ul style="list-style-type: none"> • Domestic & Commercial Bathrooms • Domestic & Commercial Kitchens • Domestic Floors • Heavy traffic areas such as: <ul style="list-style-type: none"> - Retail/Shopping Outlets - Car Showrooms - Restaurants 	<ul style="list-style-type: none"> • Sand/Cement Screed & Render • Concrete • Gypsum Plaster • Plasterboard • Underfloor Heating • Plywood • Existing Tiles • Concrete Brick/Block • Tilebacker Boards • Anhydrite Screeds • Flooring grade Asphalt & Bitumen 	<ul style="list-style-type: none"> • Porcelain • Ceramics • Terracotta • Quarry • Natural Stones • Mosaics • Composite • Quartz

Coverage chart per 5kg unit Flexigrout			
Tile Size	3mm Joint Width	5mm Joint Width	10mm Joint Width
Mosaic: 24 x 24 x 10	1.2m ²	0.8m ²	0.4m ²
150 x 150 x 8	10m ²	6m ²	3m ²
300 x 300 x 10	16m ²	10m ²	5m ²
600 x 600 x 10	30m ²	20m ²	10m ²

Water Addition:	5kg Flexigrout requires approximately 800ml of water
Pot Life at 20°C:	Approximately 45 - 60 minutes
Curing Time:	<ul style="list-style-type: none"> - Light Foot traffic after 3 - 4 hours - Flexigrout will reach final set after 24 hours - Allow 3 days before contact with heavy traffic
Colours:	See page 41
Pack Sizes:	5kg, 10kg & 20kg packs
Specification Category:	Conforms to BS EN 13888 Class CG2