

Standard Setaflex

Flexible, Standard Setting
Wall & Floor Tile Adhesive

- Flexible
- Ideal for when longer working times are required
- Excellent workability and non slip properties
- Ideal for surfaces subject to movement
- Natural Stones & Porcelain
- 3mm – 12mm bed depth
- Ideal for swimming pools and wet rooms
- Simply mix with water, no additives required



Standard Setaflex is a polymer modified, flexible, cement based wall and floor tile adhesive. Standard Setaflex has been developed for fixing a large variety of tiles to surfaces subject to limited movement and/or vibration such as plywood overlay, underfloor heating and plasterboard. Formulated to give an extended open time, Standard Setaflex is ideal where longer working times are required. It is suitable for use in areas subject to prolonged and permanent wet conditions such as swimming pools and wet rooms. Standard Setaflex is suitable for use internally and externally and is unaffected by frost after setting.

Suitable for application to:		Suitable for fixing:
<ul style="list-style-type: none"> • Sand/Cement Screed • Plywood (12mm) • Concrete • Chipboard (18mm) • Gypsum Plaster • Tilebacker Boards • Anhydrite Screeds • Plasterboard 	<ul style="list-style-type: none"> • Existing Tiles • Cement/Sand render • Underfloor Heated Screeds • Concrete Brick/Block • Electric Underfloor Heating • Vinyl Tiles/Sheets • Fibre cement sheets • Flooring grade Asphalt & Bitumen 	<ul style="list-style-type: none"> • Porcelain • Ceramics • Terracotta • Quarry • Natural Stones • Mosaics • Composite • Quartz

Water Addition:	Approximately 5 litres of water to 20kg Standard Setaflex
Coverage:	20kg will cover 5 – 6m ² at 3mm thin bed application
Pot Life at 20°C:	3 – 4 hours
Grout After:	24 - 48 hours
Colours:	Grey & White
Pack Sizes:	5kg, 10kg and 20kg packs
Specification Category:	Conforms to BS EN 12004 Class C2 TE S1