

## **EC Declaration of Performance**

In accordance with Annex III of the Regulation (EU) No. 305/2011

1. Unique identification code of the product type:

**Grout 3000 (All Colours)**

2. Type, batch or serial number or any other identifying mark to identify the construction product as required by the Article 11(4):

**Batch number: see packaging of the product**

3. Intended use of the construction product as foreseen by the manufacturer, in accordance with the applicable harmonised technical specification:

**Improved cementitious grout with additional characteristics  
of reduced water absorption and increased abrasion  
resistance**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as set out in Article 11(5):

**Tilemaster Adhesives Ltd.  
Unit 4, Tomlinson Road,  
Leyland, Lancashire.  
PR25 2DY  
United Kingdom**

5. Where applicable, the name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not relevant

6. System or systems for assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3 + 4**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**The notified body Ceram, identification No. 1289,  
has carried out the initial type testing to System 3  
and issued test Report No. (133517)-14557**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not relevant

9. Declared performance (Grout 3000):

Essential characteristics	Performance	Harmonised technical specification
Abrasion resistance	< 1000 mm <sup>3</sup>	EN 13888:2009 (E)
Flexural Strength after dry storage	>2.5 N/mm <sup>2</sup>	
Flexural Strength after Freeze-Thaw cycles	>2.5 N/mm <sup>2</sup>	
Compressive strength after dry storage	>15 N/mm <sup>2</sup>	
Compressive strength after Freeze-Thaw cycles	>15 N/mm <sup>2</sup>	
Shrinkage	<3 mm/m	
Water absorption after 30 min	<2g	
Water absorption 240 min	<5g	
Dangerous substances	See MSDS	

### Classification CG2 WA

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for on behalf of the manufacturer by:



Karl Davies  
Development Chemist

Leyland 09/10/2017